Korean Chemical Engineering Research

| gust 2020 Korean Chem. Eng. Res., 58(3) 32 Jume 58, Number 3 PISSN 0304-128X, EISSN 2233-95 | | | |
|---|---|------------|--|
| Article Process System Engineering - Plant Design - Process Sofety - Plant E | nginaaring | | |
| Process System Engineering · Plant Design · Process Safety · Plant E Human Health Risk, Environmental and Economic Assessment Based of Available Technology (BAT) for VOC Reduction in Industrial Com | on Multimedia Fugacity Model for Determination of Best plex | | |
| RFID-Based Integrated Decision Making Framework for Resource Pla Intermediates Manufacturing Plant | anning and Process Scheduling for a Pharmaceutical | 325 | |
| Experimental Study on the Changes in the Oxygen Concentration and the of the Risks of Fire and Explosion of Propylene | he Pressure at Temperature of 200 °C for the Assessment | 346 | |
| Process Design and Economics for Conversion of Kenaf to Syngas | - | 356 | |
| A Czochralski Process Design for Si-single Crystal O ₂ Impurity Minim | | 362 | |
| Level Optimization | ergy Storage Systems in a Solar-Wind Hybrid System | 369 381 | |
| Control Methods for Operation on the Saturation Edge | | | |
| Optimization of Microalgae-Based Biodiesel Supply Chain Network U | Jnder the Uncertainty in Supplying Carbon Dioxide | 390 396 | |
| Fault Detection and Diagnosis for EVA Production Processes Using A | E-SOM | 408 | |
| A Study of Standardization of Detecting Abnormal Data by Front We Power Generation Unit | ed's Shadow Effect in over 100 kW Photo Voltaic | | |
| A Study on Computing Stochastic Capacity of Energy Storage System | as using Monte Carlo Simulations | 416 424 | |
| Development of Anti-windup Techniques for Cascade Control System | 1 · · · · · | 430 | |
| Estimation of the Liability Risk for Release of Chemicals at Chemica | l Plant | 438 | |
| Biochemical Engineering · Biochip Technology · Biomedical Technol | | | |
| Quantification of DNA Delivery Efficiency Labeled with Fluorescent | Dye in Digital Electroporation System | 450 | |
| Energy/Environment · New Renewable Energy · Waste Treatment/En Analysis on Isotherm, Kinetic and Thermodynamic Properties for Ads | sorption of Acid Fuchsin Dye by Activated Carbon | 458 | |
| The Salt Removal Efficiency Characteristics of Carbon Electrodes Us in a Canacitive Deionization Process | ing Fabric Current Collector with High Tensile Strength | | |
| | C C | 466 | |
| Materials(Inorganics/Organics, Electronics, Semiconductor) · Nano Te Effects of Ingredients of Wet Etchant on Glass Slimming Process | | | |
| | | 474 | |
| Catalysis/Reaction Engineering · Reactor Development/Modeling · Simulation of Electrorheological Fluids by the Extended Maxwell-Wa | gner Polarization Model with Onsager Theory | 480 | |
| Visible Light Photocatalytic Properties of Bismuth Ferrite Prepared B | y Sol-Gel Method | 480 | |
| Short Communication | | | |
| Operating Pressure Conditions for Non-Explosion Hazards in Plants F | Iandling Propane Gas ······ Jae-Young Choi and Sang-Hoon Byeon | 493 | |

Correction

498